

MEGA BOX



A range of fully packaged cold rooms, complete with refrigeration system and shelving. Designed to meet the highest food safety and quality standards. Ideal for preservation of food products and perishable products in restaurants, pharmacies, laboratories, hospitals, butcheries, bakeries, etc., even for private purposes. Automatically operated, quiet in operation, efficient even in hardest working environment. Each unit has been individually tested and has been designed for heavy, continuous usage.

MEGA BOX		
MODEL	MCB 2.1	MFB 2.1
	CHILLER	FREEZER
SKU	0121046	0121045
VOLUME CAPACITY	2100 LITERS	2100 LITERS
EXTERNAL DIMENSION	1800 x 900 x 2000 mm	1800 x 900 x 2000 mm
POWER CONSUMPTION	760 Watt	850 Watt

We reserve the right to amend technical design and specification without prior notice

COLD ROOM



Total Food-Service Solutions

Jl. Raya Terboyo No. 15
Kawasan Industri Terboyo Megah
Semarang 50112
Tel. : +62 24 658 0573
Fax. : +62 24 659 1344; +62 24 658 0572
Email : nayati@nayati.com
Website : www.nayati.com

COLD ROOM



Optional stainless steel panels can be selected.

Standard cold rooms (type 3.1-9.0) can be supplied with standard white powder coated steel or optional stainless steel for wall-mounted rack shelving.

Maxi cold rooms (type 14-38) can be supplied with stainless steel self standing rack (modular rack shelving) as additional order.

*) These feature are available for models :
3.1 B-9.0 A m3

Features :

The fully automatic NAYATI Refrigeration units are assembled and tested in the factory. Standard units are SUITABLE FOR TROPICAL ENVIRONMENT with temperature up to +43°C. Easy maintenance with NAYATI DROP IN MACHINE SYSTEM. Efficient filter in front of condenser extends working period and make it easier to maintain. SMART DEFROST SYSTEM will automatically defrost the cold room in due time ensuring the refrigeration keep running at maximum performance. Storage temperature is thermostatically controlled and clearly displayed on digital display for easy monitoring.

All insulated wall, floor and roof panels are injected with energy efficient polyurethane insulation with 100 mm thickness. All doors are fitted with lock and robust gasket to prevent air ingress. Heater is fitted on door frame to prevent door gasket from freezing on low temperature applications. A relief valve is also fitted to freezer operation.

SAFETY is ensured with internal safety release door latch. Standard cold rooms are supplied with non-slip floor for heavy duty application. Cold and chill temperature rooms can be supplied without a floor for trolley operation. Room for fish storage can be supplied with special floor including drainage facility.

Standard cold rooms are supplied with white coated steel interior and exterior panels. These panels are EASY TO CLEAN and MAINTAIN.

	Depth 1200 mm	Depth 1500 mm	Depth 1800 mm	Depth 2100 mm	Depth 2400 mm	Depth 3000 mm	Depth 3600 mm	Depth 4200 mm	Depth 4800 mm	Depth 5400 mm	Depth 6000 mm
Width 1800 mm	3,1B	4,0B	5,0A	5,9A	6,7A						
Width 2100 mm	3,7B	4,8B	5,9B	8,0A							
Width 2400 mm	4,3B	5,5B	6,7B	8,0B	9,0A	14	17	20	23	27	30
Width 3000 mm		7,0B	8,5B			18	22	26	29	33	38

	Depth (mm) 1200	1500	1800	2100	2400	3000	3600	4200	4800	5400	6000
Height 2200mm (Model 9,0A & smaller) or Height 2400mm (Model 14 & larger)											
Width (mm) 1800	3,1B	4,0B	5,0A	5,9A	6,7A						
2100	3,7B	4,8B	5,9B	8,0A							
2400	4,3B	5,5B	6,7B	8,0B	9,0A	14	17	20	23	27	30
3000		7,0B	8,5B			18	22	26	29	33	38

*C = Chiller, F = Freezer

COLD ROOM								
MODEL	DIMENSION (mm)			ENERGY USAGE (kW/H)		COOLING CAPACITY (KCal/H)		VOLUME (L)
	W	D	H	C	F	C	F	
3.1 B	1.800	1.200	2.200	1.2	1.4	1.4	1.1	3.200
3.7 B	2.100	1.200	2.200	1.2	1.4	1.4	1.1	3.800
4.0 B	1.800	1.500	2.200	1.2	1.4	1.4	1.1	4.100
4.3 B	2.400	1.200	2.200	1.2	1.4	1.4	1.1	4.400
4.8 B	2.100	1.500	2.200	1.2	1.4	1.4	1.1	4.900
5.0 A	1.800	1.800	2.200	1.5	2.8	1.6	1.7	5.100
5.5 B	2.400	1.500	2.200	1.5	2.8	1.6	1.7	5.700
5.9 A	1.800	2.100	2.200	1.5	2.8	1.6	1.7	6.000
5.9 B	2.100	1.800	2.200	1.5	2.8	1.6	1.7	6.000
6.7 A	1.800	2.400	2.200	1.5	2.8	1.6	1.7	7.000
6.7 B	2.400	1.800	2.200	1.5	2.8	1.6	1.7	7.000
7.0 B	3.000	1.500	2.200	1.5	2.8	1.6	1.7	7.200
8.0 A	2.100	2.400	2.200	1.5	2.8	1.6	1.7	8.300
8.0 B	2.400	2.100	2.200	1.5	2.8	1.6	1.7	8.300
8.5 B	3.000	1.800	2.200	1.5	2.8	1.6	1.7	8.900
9.0 A	2.400	2.400	2.200	1.5	2.8	1.6	1.7	9.600
14	2.400	3.000	2.400					13.500
17	2.400	3.600	2.400					16.400
18	3.000	3.000	2.400					17.200
20	2.400	4.200	2.400					19.300
22	3.000	3.600	2.400					20.900
23	2.400	4.800	2.400					22.200
26	3.000	4.200	2.400					24.600
27	2.400	5.400	2.400					25.100
29	3.000	4.800	2.400					28.300
30	2.400	6.000	2.400					28.000
33	3.000	5.400	2.400					32.000
38	3.000	6.000	2.400					35.700

ON REQUEST