

Total Food Service Solutions

Modular Cooking - Meritus Gas - Hot Top NGHT 8-75 (ME)



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Modular gas hot top with 750 mm depth, powered with 5.7 kW chrome-plated burner. Static 2/1 GN gas oven with 6.5 kW tubular burner.

Usable for boiling, steaming, frying, braising, simmering and steam frying. Oven module usable for roasting and baking.

Made of AISI 304 with 1.5 mm top thickness, griddle is made of Molybdenum steel (16Mo5) with 18 mm thickness, powered with circular cast iron burner that heats up the hot top in concentric distribution. Central temperature can reach up to 550 degree Celcius.

OTHER AVAILABLE MODELS

- NGHT 4-75 (ME)
- NGHT 8-75 OC (ME)
- NGHT 12-75 4OB (ME)
- NGHT 12-75 (ME)
- NGHT 12-75 OC (ME)

MAIN FEATURES

- Powered with 10 kW chrome-plated steel tubular burner.
- Hot top griddle is made of 18 mm thick Molybdenum steel for high thermal performance.
- Concentric heat distribution. Center temperature can reach up to 550 degree Celcius. Griddle center can be removed for service, usable for wok cooking.
- Piezzo ignition system with rubber cover.
- Equipped with flame failure device.

CONSTRUCTION

- External construction entirely with AISI 304.
- Top panel with 1.5 mm thickness. Orbital surface finishing: resistant toward scratches.
- Front panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- Side panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- · Adjustable +/- 25 mm AISI leg.
- Nayati connection system between Meritus products on the front panels, cabinets, and splashbacks.
- · Cabinet executed with H2 radius.
- Deep drawn front panel to minimize liquid penetration to the internal part.
- Gasket protection behind the knobs to prevent water to seeping in, prolonging main heating regulation parts.

INCLUDED ACCESSORIES

- G20 Conversion Kit
- SS Hook to remove griddle inner plate.
- 2/1 GN oven wire tray (1 pcs.).

OPTIONAL ACCESSORIES


· Joint clip ME.

PT. NAYATI INDONESIA


www.nayati.com


Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.





TOP





*Overall dimension in mm

TECHNICAL DATA External Dimensions

 Width
 : 800 mm

 Depth
 : 750 mm

 Height
 : 850/910 mm

Cooking Surface

Cooking zones : Hot Top: 745 x 580 mm, Oven: 540

x 666. mm

Gas Power Rating

Heat input total : LPG/Natural Gas 16.5 kW

No. of burners : 2

Control type : Hot plate: High - low power con-

troll, Oven: Modulating tempera-

ture control

Gas type options : LPG G30, G31

Natural Gas G20, G25, G25.3

Connections

Gas : DN 20 (3/4")

Water : N/A Drain : N/A

Heat & Steam Emissions

Direct heat emission : 5.28 kW
Latent heat emission : 2.5 kW
Steam emission : 3.67 kg/h

PACKAGING DATA

 Width
 : 830 mm

 Depth
 : 780 mm

 Height
 : 1020 mm

 Volume
 : 0.66 m³

WEIGHT

Net Weight : 177 kg Gross Weight : 186 kg

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 23/03/2021