

Total Food Service Solutions

Smart Oven - Proofer Electric - Proofer NBP 15-RL



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Electric Proofer with the roll-in capacity of 15 bakery trays.

Designed to be used along with Bakomatic Bakery Convection/Deck/Pizza Oven Series.

Roll-in cabinet design with chamber dimension of 598 x 747 x 1789 mm.

OTHER AVAILABLE MODELS

- NBP 16-S
- NBP 36-RL

MAIN FEATURES

- Proofing temperature range of 30 to 45 degree Celcius.
- Humidty settings range from 0 to 100%.
- Equipped with ramp for tray trolley access.
- Door is completed with durable gasket to prevent temperature/humidity from seeping out.
- Framed door with glass window to observe proofing results.
- Controlled with seven-segment interface for time, temperature and humidity display and adjustment.
- Proofing capacity tested for 240 pieces of 30 gram-croissants.
- Proofing capacity tested for 180 pieces of 35 gram-danish raisin.

CONSTRUCTION

Exterior panel constructed from stainless steel 304.

- Tempered glass door made of single layer to insulate heat inside the chamber.
- Stainless steel plinth base with ramp.

INCLUDED ACCESSORIES

Bakery tray runners.

OPTIONAL ACCESSORIES

• Trolley for bakery tray NBCR 460.


PT. NAYATI INDONESIA

www.nayati.com


Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.



TOP



700 1012 436



*Overall dimension in mm

TECHNICAL DATA

External Dimensions

Width : 700 mm Depth : 1070 mm Height : 1995 mm

Cooking Surface

Cooking zones : 15 bakery trays of 400 x 600 mm.

Heating zones

Control type : Temperature and Timer control

Electrical Supply Data

Total connected load : 1.8 kW

: 230V, 1NPE AC / 50-60 Hz Voltage

Recommended fuse : 0.5 A (slow)

Connections

: DN 20 (3/4") Water Drain : DN 10 (3/8")

Heat & Steam Emissions

Direct heat emission : 0.22 kW Latent heat emission : 0.32 kW Steam emission : 0.48 kg/h

PACKAGING DATA

Width : 770 mm Depth : 1115 mm Height : 2140 mm Volume : 1.84 m³

WEIGHT

Net Weight : 139.5 kg **Gross Weight** : 186.5 kg

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 23/01/2021