
Total Food Service Solutions

Modular Cooking - Amicus

Electric - Fry Top

NEFT 4-60 AM



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Table top electric fry top with 600 mm depth and 3.9 kW Steady-State Surface heater (SSS)

Usable for contact grilling and starch cooking.

Made of AISI 304 with 1.2 mm top thickness, equipped with temperature control, AISI 420 griddle with 16 mm thickness and oil drawer.

OTHER AVAILABLE MODELS

- N/A

MAIN FEATURES

- Powered with 3.9 kW Steady-State Surface heater (SSS)
- Griddle made of AISI 420 with thickness of 16 mm, preventing rust.
- Griddle can be configured with groove for producing grill mark or with hard chrome plating for fish grilling.
- Obround drain with oil collection drawer included.
- Thermal-cut off when overheated.
- Fully-welded griddle to the top surface.

CONSTRUCTION

- External construction entirely with AISI 304.
- Top panel with 1.2 mm thickness. Orbital surface finishing: resistant toward scratches.
- Side panel with 1.2 mm deep-drawn surface.
- Front panel with 0.8 mm deep-drawn surface.
- Top panel with Orbital scratch-preventing finish.
- Rubber leg with 40 mm height
- Connector between Amicus product on the back.
- IPX4 water protection level.

INCLUDED ACCESSORIES

- Splashguard
- Power cable, H07RN-F (3x 2.5 mm).
- Amicus joining clip.


OPTIONAL ACCESSORIES

- N/A


PT. NAYATI INDONESIA
www.nayati.com
Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.

Total Food Service Solutions


FRONT



TOP



SIDE



Electric Connection

*Overall dimension in mm

TECHNICAL DATA

External Dimensions

Width	: 380 mm
Depth	: 600 mm
Height	: 260/312 mm

Cooking Surface

Cooking zones	: 310 x 480 mm
Heating zones	: 1
Control type	: Modulating temperature control

Electrical Supply Data

Total connected load	: 3.9 kW
Voltage	: 230V, 1NPE AC / 50-60 Hz
Recommended fuse	: 20 A (slow)

Connections

Water	: N/A
Drain	: N/A

Heat & Steam Emissions

Direct heat emission	: 1.3 kW
Latent heat emission	: 1.6 kW
Steam emission	: 2.3 kg/h

PACKAGING DATA

Width	: 410 mm
Depth	: 630 mm
Height	: 432 mm
Volume	: 0.11 m^3

WEIGHT

Net Weight	: 33 kg
Gross Weight	: 37 kg

PT. NAYATI INDONESIA
www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.

07/06/2021

Total Food Service Solutions

Modular Cooking - Amicus
Electric - Fry Top
NEFT 4-60 AM