

## Modular Cooking - Meritus

### Electric - Hot Plate

#### NEHP 8-75 (ME)



Due to continuous technical development, the image shown may not represent the latest design of the unit.

#### DESCRIPTION

Modular electric hot plate with 750 mm depth, powered with 4 x 2.6 kW hot plate cast iron heaters. Static 2/1 GN electric oven with 6 kW heater. Usable for boiling, steaming, frying, braising, simmering and steam frying. Oven module usable for roasting and baking.

Made of AISI 304 with 1.5 mm top thickness, equipped with deep drawn collared square hot plate element. Oven is sized for 2/1 GN with reflective AISI cavity for superior heat transfer.

#### OTHER AVAILABLE MODELS

- NEHP 4-75 (ME)
- NEHP 8-75 OC (ME)
- NEHP 12-75 OC (ME)
- NEHP 12-75 (ME)

#### MAIN FEATURES

- Powered with 4 x 2.6 kW square hot plate element.
- Static 2/1 GN electric oven is powered with 6 kW incoloy heater 2/1 GN cavity and reflective AISI chamber to improve thermal efficiency. Designed with deep-drawn chamber that requires no gasket for maintenance.
- Rectangular hot plate with 220 x 220 mm designed for performance.
- Six levels of heating.
- Collared hot plate for better durability.
- Heating zones are recessed to minimized spillage.

#### CONSTRUCTION

- External construction entirely with AISI 304.
- Top panel with 1.5 mm thickness. Orbital surface finishing: resistant toward scratches.
- Front panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- Side panel is constructed of 0.8 mm AISI 304 with satin surface finish.
- Adjustable +/- 25 mm AISI leg.
- Nayati connection system between Meritus products on the front panels, cabinets, and splashbacks.
- Cabinet executed with H2 radius.
- Deep drawn front panel to minimize liquid penetration to the internal part.
- Gasket protection behind the knobs to prevent water to seeping in, prolonging main heating regulation parts.
- IPX5 water protection level.


#### INCLUDED ACCESSORIES

- 2/1 GN oven wire tray (1 pcs.).


#### OPTIONAL ACCESSORIES

- Power cable, H07RN-F (5 x 6 mm) p/mtr.
- Joint clip ME.


## FRONT



## TOP



## SIDE



\*Overall dimension in mm

## TECHNICAL DATA

### External Dimensions

Width	: 800 mm
Depth	: 750 mm
Height	: 850/870 mm

### Cooking Surface

Cooking zones	: Hot Plate = 4 x 260 x 260, Oven = 575 x 666 mm
Heating zones	: 6
Control type	: Hot plate: Modulating power control, Oven: Modulating temperature control

### Electrical Supply Data

Total connected load	: 16.4 kW
Voltage	: 400V, 3NPE AC /50-60Hz
Recommended fuse	: 25 A (slow)

### Connections

Water	: N/A
Drain	: N/A

### Heat & Steam Emissions

Direct heat emission	: 4.8 kW
Latent heat emission	: 2.06 kW
Steam emission	: 3.03 kg/h

### PACKAGING DATA

Width	: 830 mm
Depth	: 780 mm
Height	: 990 mm
Volume	: 0.64 m <sup>3</sup>

### WEIGHT

Net Weight	: 159 kg
Gross Weight	: 180 kg

PT. NAYATI INDONESIA

[www.nayati.com](http://www.nayati.com)

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.

11/09/2020