

Total Food Service Solutions

Smart Oven - Pizza Oven Electric - Pizza Oven NEPO 50.50-S



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Electric Pizza Oven with the chamber size of 50 cm by 50 cm. Powered with two heating element with total power rate of 3.1 kW.

Usable for a single pizza with 30 cm or 45 cm diameter.

Temperature of upper and lower chamber is controlled separately through digital controller. Equipped with timer indicator. Maximum working temperature of 400 degree Celcius. Equipped with oven lamp for visualization. Can be mounted above cabinet NBSO 50.

OTHER AVAILABLE MODELS

- NEPO 80.70-S
- NEPO 105.65-S

MAIN FEATURES

- Heated with maximum temperature of 400 degree Celcius.
- Includes halogen lighting inside the chamber for visualization.
- Lower opening oven door with stainless steel cylindrical handle bar.
- Base of the chamber is made of durable refractory stone.
- Individual temperature control function, each for upper and lower chamber.
- Equipped with safety thermostat to prevent overheating.
- · Includes digital timer indicator.
- · Possibility to stack with dedicated stand.
- Possibility to configure double-deck pizza oven.

CONSTRUCTION

- Exterior panel constructed from stainless steel 304.
- Tempered glass door made of double layer to insulate heat inside the chamber.
- Round bar stainless steel door handle.

INCLUDED ACCESSORIES

Power cable.

OPTIONAL ACCESSORIES

• NBSO 50

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.



FRONT

TECHNICAL DATA **External Dimensions**

Width : 727 mm Depth : 638 mm Height : 374 mm

Cooking Surface

Cooking zones : 500 x 500 mm Heating zones : 2 x 1.55 kW

Control type : Temperature control

Electrical Supply Data

Total connected load : 3.1 kW

: 230V, 1NPE AC / 50-60 Hz Voltage

Recommended fuse : 6 A (slow)

Connections

: N/A Water Drain : N/A

Heat & Steam Emissions


Direct heat emission : 1.1 kW Latent heat emission : 0.5 kW Steam emission : 0.7 kg/h

PACKAGING DATA


Width : 818 mm Depth : 810 mm Height : 515 mm Volume : 0.34 m³

WEIGHT


Net Weight : 50 kg **Gross Weight** : 66 kg



TOP



SIDE



*Overall dimension in mm

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 09/05/2020 NEPO 50.50-S