

Total Food Service Solutions

Asian Cooking - Gas Steamer Gas - Dim Sum Steamer NGSB 9-90 CE



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Gas dim sum steamer with one steaming engine for seven dim sum trays steaming capacity. Equipped with high-performance premix burners of a total of 42 kW power rate for quick steam and a low combustion noise of below 70 dBA.

Three steaming operations to achieve the ideal balance between performance and energy-saving when needed. The cold-water supply with one swivel faucet mounted on the backsplash, and the deck cooling & cleaning system guarantees easy cleaning and a maximum of hygiene.

Powerful and suitable for mass production of dim sum and steamed food, the NGSB steamer is the perfect choice for all Asian restaurants.

OTHER AVAILABLE MODELS

N/A

MAIN FEATURES

- High-performance premix burners with blowers and a total power rate of 42 kW. Low combustion noise of <70 dB.
- · Electric ignition.
- Equipped with gas valves, gas failure security and gas knob.
- Slanted, deep drawn, reinforced top panel with drain channel and removable strainer in the front for easy operation.
- Deck cooling & cleaning system with spray nozzles for a maximum hygiene and easy operation.
- Cold-water supply with one swivel faucet mounted on the backsplash.
- Steam box engine with automatic filling system and security thermostat.
- CE certified unit.

CONSTRUCTION

- Sturdy frame made of stainless steel AISI 430.
- Slanted, reinforced deep drawn stainless steel top panel (3.2 mm), AISI 304 with hairline surface pattern.
- Front and side panels made of stainless steel AISI 304 with hairline surface pattern (0.8 mm).
- Backsplash made of stainless steel AISI 304 with hairline surface pattern (1.2 mm).
- Tubular, height adjustable (±25 mm) stainless steel legs.
- Types of installations: free standing or placed on a plinth.
- Frame, top and panels, all made of high-grade stainless steel.

INCLUDED ACCESSORIES

Dim sum plate with seven holes.

OPTIONAL ACCESSORIES

 Dim sum tray kit - two levels with lid for max. 24 pcs bamboo trays Ø 130 mm.


PT. NAYATI INDONESIA

www.nayati.com


Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.



TOP



SIDE



*Overall dimension in mm

TECHNICAL DATA

External Dimensions

Width : 900 mm Depth : 900 mm Height : 750/1200 mm

Cooking Surface

Cooking zones : Ø 600 mm

Gas Power Rating

Heat input total : LPG/Natural Gas 42 kW, and 0.08 kW

- 230V, 1NPE AC / 50-60 Hz

No. of burners

Control type : High-low power control

Gas type options: LPG G30, G31

Natural Gas G20, G25

Electrical Supply Data

Total connected load : 0.08 kW

Voltage : 230V, 1PNE AC / 50-60 Hz

Recommended fuse : 6 A (slow)

Connections

Gas : DN25 (1") Water : DN20 (3/4")

Drain : DN20 (3/4") & DN40 (1 1/2")

Heat & Steam Emissions

Direct heat emission : LPG/Natural Gas 6.30 kW : LPG/Natural Gas 7.56 kW Latent heat emission Steam emission : LPG/Natural Gas 11.13

kg/h

PACKAGING DATA

Width : 930 mm Depth : 930 mm Height : 1320 mm Volume : 1.14 m³

WEIGHT

Net Weight : 149 kg **Gross Weight** : 213 kg

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 16/02/2023