

Total Food Service Solutions

Smart Oven - Pizza Oven Gas - Pizza Oven NGPO 60.60-S



Due to continuous technical development, the image shown may not represent the latest design of the unit.

DESCRIPTION

Gas Pizza Oven with the chamber size of 60 cm by 60 cm. Powered with double gas burner with total power rate of 16.1 kW.

Usable for a single pizza with 30 cm or 45 cm diameter.

Equipped with temperature control and timer indicator. Black-coated stainless steel casing compliments the outlook of the oven. Portable and versatile, suitable for compact setups.

OTHER AVAILABLE MODELS

• NGPO 110.74-S

MAIN FEATURES

- Heated with maximum temperature of 450 degree Celcius.
- Includes halogen lighting inside the chamber for visualization.
- Lower opening oven door with stainless steel cylindrical handle bar.
- Base of the chamber is made of durable refractory stone.
- Ignited through semi-automatic piezzo ignition.
- Lower and upper burners are controlled independently to achieve a perfect pizza results.
- Digital temperature control function.
- Equipped with safety thermostat to prevent overheating.
- · Possibility to stack with dedicated stand.
- Possibility to configure double-deck pizza oven.

CONSTRUCTION

- Exterior panel constructed from stainless steel 304
- Tempered glass door made of double layer to insulate heat inside the chamber.
- · Round bar stainless steel door handle.

INCLUDED ACCESSORIES

· Power cable.

OPTIONAL ACCESSORIES


NPSO 60

PT. NAYATI INDONESIA


www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.

TOP



SIDE



*Overall dimension in mm

TECHNICAL DATA

External Dimensions

Width : 1002 mm Depth : 1057 mm Height : 541 mm

Cooking Surface

Cooking zones : 600 x 600 mm

Gas Power Rating

Heat input total : LPG/LNG 16.1 kW

No. of burners : 4

: Temperature control Control type

Gas type options: LPG G30, G31

LNG G20, G25

Electrical Supply Data

Total connected load : 0.03 kW

Voltage : 230V, 1NPE AC / 50-60 Hz

Recommended fuse : 6 A (slow)

Connections

Gas : DN 20 (3/4")

Water : N/A : N/A Drain

Heat & Steam Emissions

Direct heat emission : LPG/LNG 5.64 Kw Latent heat emission : LPG/LNG 3.22 Kw : LPG/LNG 4.7334 kg/h Steam emission

PACKAGING DATA

Width : 1040 mm Depth : 1135 mm Height : 700 mm Volume : 0.83 m³

WEIGHT

Net Weight : 100 kg **Gross Weight** : 133.6 kg

PT. NAYATI INDONESIA

www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 09/05/2020