

### **Total Food Service Solutions**

# Oriental Cooking - Wok Range Gas - Wok Kwalie / CE NGK S 80-75 W2



Due to continuous technical development, the image shown may not represent the latest design of the unit.

### **DESCRIPTION**

Gas wok with two high-performance jet-burners, each with a power rate of 33 kW. Compact, powerful and suitable for various methods of Oriental cooking, the NGK wok is the perfect choice for any kitchen.

Made of stainless steel AISI 304 with a slanted, deep drawn 3.2 mm strong, reinforced top panel with heavy-duty removable cast iron wok rings. Cold-water supply with two swivel faucets, mounted on the backsplash, easily operable from the front panel.

The intelligent deck cooling & cleaning system with spray nozzles guarantee an efficient cooling of the top panel and an enhanced hygienic as food debris are flushed away towards the drain channel in the back. The built-in strainer avoids congestions of the drain.

#### OTHER AVAILABLE MODELS

- NGK S 40-75 W1
- NGK S 120-75 W3
- NGK S 40-90 W1
- NGK S 40-90 W1S1
- NGK S 80-90 W2S1
- NGK S 80-90 W2S2

#### MAIN FEATURES

- Two atmospheric jet-burners with a power rate of 33 kW each.
- · Manual ignition.
- Equipped with pilot burners, safety thermocouples, gas valves, gas knee levers.
- Slanted, deep drawn, reinforced (3.2 mm) top panel with drain channel and removable strainer in the back for easy operation.
- Cold-water supply with two swivel faucets mounted on the backsplash.
- Deck cooling & cleaning system with spray nozzles for maximum hygiene.
- Suitable for wok-pan sizes Ø 14-18" (355-457 mm).
- · CE certified unit.

#### **CONSTRUCTION**

- Sturdy frame made of stainless steel AISI 430.
- Slanted, reinforced deep drawn stainless steel top panel (3.2 mm), AISI 304 with hairline surface pattern.
- Front and side panels made of stainless steel AISI 304 with hairline surface pattern (0.8 mm).
- Backsplash made of stainless steel AISI 304 with hairline surface pattern (1.2 mm).
- Tubular, height adjustable (±25 mm) stainless steel legs.
- Type of installation: free standing.
- Frame, top and panels, all made of high-grade stainless steel.

### **INCLUDED ACCESSORIES**

Wok stand (2 pcs)

## **OPTIONAL ACCESSORIES**

- Burner nozzle kit converts the wok burner power rate from 33 kW to 24 kW.
- Condiment tray made of stainless steel AISI 304 (300x300 mm).

### PT. NAYATI INDONESIA

### www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions.



Cooking Surface

Wok burners : 2 x Ø 280 mm

Soup burners : N/A

**Gas Power Rating** 

Heat input total : LPG/LNG 66 kW

No. of burners : 2

Control type : Open-close valve Gas type options: LPG G30, G31

LNG G20, G25

Connections

Gas : DN 20 (3/4") Water : DN15 (1/2") Drain : DN25 (1")

**Heat & Steam Emissions** 


Direct heat emission : LPG/LNG 16.50 kW Latent heat emission : LPG/LNG 9.90 kW Steam emission : LPG/LNG 17.49 kg/h

PACKAGING DATA


Width : 1430 mm Depth : 780 mm Height : 1170 mm Volume : 1.31 m<sup>3</sup>

WEIGHT


Net Weight : 116 kg **Gross Weight** : 149 kg



**TOP** 



# SIDE



\*Overall dimension in mm

## PT. NAYATI INDONESIA

### www.nayati.com

Nayati reserves the right to make product alterations and or price adjustments at any time and can not be held responsible for any printing errors or omissions. 30/09/2020